

Bases, Filters



RAB-PO-Xxx-XN, RAC-PO-Xxx-XN, RAB-PO-Xxx-XD, RAC-PO-Xxx-XD

The base is fully universal, which means that it is usable for all types of free-standing cabinets except ROA and RSX. The construction of the base is formed of two side profiles which correspond to the depth of the cabinet, and two cover panels (front and back) with a corresponding width. Bases **XN**series have a load capacity of **400 kg**, bases **XD**series have a load capacity **1500 kg**.

Supply includes

- 2x side base profile with a cable entry
(with breakout-type blanking panels)
- 2x cover with cable openings
(with breakout-type blanking panels)
- 1 x cover with a filter
- 1 x anti-dust brush
- fasteners

The bases are delivered dismantled. The second dust filter for the second cover replacing can be easily ordered later. The base always exactly copies the ground plan of the cabinet regardless of installation of filter. The bases are standardly supplied in widths of 600 and 800 mm and depths from 600 to 1200 mm. All the bases are 120 mm high.

TIP: The base is prepared for installation of stabilisers, which are highly recommended to use on cabinets with sliding servers.

.....



Type XN	Dimensions (mm)	maximum recommended load (kg)
---------	-----------------	-------------------------------

RAx-PO-X66-XN	600 x 600	400
RAx-PO-X68-XN	600 x 800	400
RAx-PO-X69-XN	600 x 900	400
RAx-PO-X61-XN	600 x 1000	400
RAx-PO-X60-XN	600 x 1100	400
RAx-PO-X62-XN	600 x 1200	400
RAx-PO-X86-XN	800 x 600	400
RAx-PO-X88-XN	800 x 800	400
RAx-PO-X89-XN	800 x 900	400
RAx-PO-X81-XN	800 x 1000	400
RAx-PO-X80-XN	800 x 1100	400
RAx-PO-X82-XN	800 x 1200	400

Type XD	Dimensions (mm)	maximum recommended load (kg)
RAx-PO-X68-XD	600 x 800	1500
RAx-PO-X61-XD	600 x 1000	1500
RAx-PO-X60-XD	600 x 1100	1500
RAx-PO-X62-XD	600 x 1200	1500
RAx-PO-X88-XD	800 x 800	1500
RAx-PO-X81-XD	800 x 1000	1500
RAx-PO-X80-XD	800 x 1100	1500
RAx-PO-X82-XD	800 x 1200	1500